



KAPLAN POWER YOUR FUTURE

MANUFACTURING HIGHEST QUALITY GENERATORS

Powered By: SDEC

Model: KPS700 | Engine: JSD565TAD | Controller: D300

www.kaplanpower.com
info@kaplanpower.com



Standby Ratings [ESP]

Thee Phase Rating, 50HZ, PF 0.8, Noise Level 75 dBA

Voltage	KVa	KW
400/230	700.00	560.00

Standard Features

- 4 Stroke, 1500 RPM, water cooled heavy duty diesel engine
- Protection system on Manuel run
- Flexible oil pipes and oil draining valve
- Pre-heater
- Lubrication oil and anti-freeze
- Batteries and cables
- Electrostatic paint coated, steel, welded chassis
- Fuel tank housed in the chassis
- Industrial type silencer
- Electronic battery charger
- Electrical wiring diagram
- User manual and operating manual
- Automatic working time 10 second

Optional Equipment

Engine

- Remote Radiator Cooling
- Oil heater
- Fuel-Water Separator Filter

Alternator

- Main line circuit breaker
- Anti-Condensation Heater
- Over sized alternator

Control System

- Remote communication with modem
- Alarm output relays/ Charge Ammeter
- Automatic synchronizing



Others Accessories [Optional]

- Automatic transfer switch
- Remote control and monitoring
- Alarm system for fuel level
- Trailer
- 1 Phase - 3 Phase switch plugs
- 1500/3000 hours maintenance kit
- Tool kit for maintenance
- Inlet and outlet acoustic baffles
- Inlet and outlet motorized louvers
- Main Fuel Tank
- Supplied with oil and coolant - 30 °C

**Stand By
Power**

Supplying of emergency electrical power at variable load, in the event of normal utility power failure. This rating is maximum power, no overload capability is available.

**Prime
Power**

Supplying of electrical power at variable load for an unlimited number of hours in the event of normal utility power failure. 10% over load capability is available.

Diesel Engine Specifications


Manufacturer	SDEC
Model	JSD565TAD
No. of Cylinders & Build	12 Cylinder, In Line
Aspiration and Cooling	Water
Maximum Standby Power	560 Kw
Total Displacement	26.6 L
Bore & Stroke	135x155 mm
Compression Ratio	16:1
Rated Speed [RPM]	1500 rpm
Governor	Electronic
Oil Capacity	65 L
Coolant Capacity	48 L
Start System	24 V D.c.
Fuel Consumption	100% Load
L/H	126

Replaceable cylinder jacket
Dry type replaceable oil filter
Heat-resistant radiator for 50 °C

Alternator Specifications

Make	KAPLAN POWER
Model	KPS 700
Short Circuit Current	> 300%
Frequency	50 Hz
Power	700 kVa
Design	Brushless, 4 Poles
Phase	3P
Voltage	400/230 V
Current	1008 A
Insulation Class	H
Stator	2 / 3 steps
Rotor	Single Bearing System
Excitation System	Electronic AVR
Stationary Voltage Regulation	1% (+/-)
Connection Type	Star

4 Poles, Self-Excitation, Brushless, Synchron type alternator
Electronic type automatic voltage regulator (AVR)
Self Cooled



- 1. Steel Structures**
- 2. Emergency stop bush button**
- 3. Control panel to be place both right and front**
- 4. Corrosion resistant locks and hinges**
- 5. Sound proof foam material**

Introduction

Sound proof authenticated and Weather insulated Enclosures for generating sets from Kaplan, meet event the sound requirements and provide optimum protection from inclement weather and development by our specialist acoustic engineers. Our modular designed sound insulated canopies provide ease of access for servicing and general maintenance and interchangeable components permitting on-site repair. Enclosures are designed to optimize genset cooling performance, providing you with confidence that genset ratings and ambient capability.

Standard Specifications

1. Compact footprint, low profile design.
2. Exhaust system inside canopy
3. Large doors on each side
4. Body made from steel components treated with polyester powder coating
5. Lifting points on the base frame
6. Kaplan makes its generating sets' noise level tests in accordance with directive 2000/14/EC validation of the noise level

Width	mm	2780
Length	mm	4200
Height	mm	1700
Standard Fuel Tank	L	1000-1200

WARNING


Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.

www.kaplanpower.com | +90(850)2550307

Dimensions With Canopy

Dimensions & Weight


Length (L)	mm	4200
Height (H)	Mm	1700
Width (W)	Mm	2780
Net Weight	Kg	4795
Standard Fuel Tank	L	1000-1250



Dimensions Without Canopy

Dimensions & Weight

Length (L)	mm	3750
Height (H)	Mm	1700
Width (W)	Mm	2170
Net Weight	Kg	4165
Standard Fuel Tank	L	1000-1250



Control Panel Features



- Diesel and gas genset support
- 400Hz operation support
- 400 event logs, full snapshot
- All parameters front panel editable
- 3 level configuration password
- 128x64 graphical LCD display
- Downloadable language
- Waveform display of V & I
- Harmonic analysis of V & I
- Synchroscope & check synch
- Allows closed transfers
- 16Amp MCB & GCB outputs
- 8 configurable digital outputs
- Outputs expandable to 40
- 4 configurable analog inputs
- Both CANBUS-J1939 & MPU
- 3 configurable service alarms
- Multiple nominal conditions
- Multiple automatic exerciser

- Weekly operation schedule
- Dual mutual standby with equal aging of gensets
- Manual "speed fine adjust" on selected ECUs
- Automatic fuel pump control
- Disable protections feature
- Excess power protection
- Reverse power protection
- Overload IDMT protection
- Load shedding, dummy load
- Multiple load management
- Current unbalance protection
- Voltage unbalance protection
- Fuel filling & fuel theft alarms
- Battery back-up real time clock
- Idle speed control
- Battery charge run enabled
- Combat mode support

- Contactor & MCB drive
- 4 quadrant power counters
- Mains power counters
- Fuel filling counter
- Fuel consumption counter
- Modem & Ethernet diagnostics
- Configurable through USB, RS-485, Ethernet and GPRS
- Free configuration program
- Allows SMS controls
- Ready for central monitoring Ethernet and GPRS
- Mobile genset support
- Automatic GSM geo-location
- GPS connectivity (USB & RS232)
- Dynamic DNS support
- Easy USB firmware upgrade
- IP65 rating with standard gaske


Optional Features & Accessories

Double Wall Fuel Tank

- Fiberglass Cladding
- Metric Rod

Additional Devices

- Device for detecting fuel leaks
- Fuel level detection (OCIO)
- Fuel level detection (OCIO) with Controller for PC



Head office

Şerifali Mahallesi, Kutup sk No:11 34775
Ümraniye/İstanbul Turkey

Pakistan Office

Office No. 306, 3rd floor, Arooj Arcade F-10
Markaz, Islamabad - Pakistan